









Heavy-duty, lightweight with readout, • New hold feature freezes display for later Sylvac's Digital Scales are equipped with a fixing clamp on both ends. It can be mounted by four M5 screwscenter distance of holes .71"(18mm). Two tapped M3 holes on each side of the housing allow mounting to appropriate equipment.

Special Features:

- Section of scale: 1.26 x .31" (32 x 8mm).
- Dimensions of housing: 4.72 x 2.76 x .83" (120 x 70 x 21mm).
- The main beam is hardened stainless steel box construction filled with epoxy resin for stability, strength and lightness.

- viewing. Ideal for hard to reach places.
- Incremental floating zero. Deviations are read out directly with no math.
- Large, high-contrast LCD display indicates in/ mm, hold and zero functions.
- New low drain, high efficiency lithium wafer battery offers 4500 hrs. continuous on time.
- Direct inch/metric conversion.
- Direct RS232C output connects tool to any computer or printer without an interface.



Order No.	Range	"A" Overall Length	Accuracy
54-998-108	8"/200mm	16"/400mm	.0015"
54-998-112	12"/300mm	20"/500mm	.0015"
54-998-120	20"/500mm	28"/700mm	.002"
54-998-124	24"/600mm	32"/800mm	.002"
54-998-130	32"/800mm	40"/1000mm	.0025"
54-998-140	40"/1000mm	48"/1200mm	.0025"
54-115-333	Simplex Connecting Kit. Includes 80"(2m) connecting cable with 9 pin		
	IBM compatible, 9/25 pin adaptor, support disk and instruction book.		
54-100-350	Replacement Lithium battery (type #CR2030 or BR2032)		