



Model	54-060-024	54-065-024	54-070-024
Measuring range	24"(600mm)	24"(600mm)	24"(600mm)
L	C + 2.5% + 120mm	C + 2.5% + 130mm	C + 2.5% + 164mm
Α	L -16	L -16	L -16



## Digital Cylindrical Beam Scales

Fowler/Sylvac's Digital High Accuracy, high precision, cylindrical scales with RS232C output are available in two styles. Horizontal scale #54-060-024 and vertical scale #54-065-024 feature rectangular LCD readouts similar to our OEM scales (#54-050 series.) The #54-070-024 cylindrical scale features a round face similar to the Mark IV Ultra-digit Indicator which rotates in either a horizontal or vertical position.

- Hold feature freezes display for later viewing. Direct inch/metric conversion.
- Zero button may be reconfigured as a hold button. If tool is used for SPC, it'll automatically be configured as a data output switch.
- Low drain, high efficiency lithium wafer battery offers 4500 hrs. of continuous on time. Life extended 2-3 years with use of on/ off switch.
- Direct RS-232C serial output. Allows connection of the scale to any computer or serial printer with no interface necessary!



п		ı
ш	_	
ш	_	
ш	_	
ш	_	ı
	- 12	

Order No.	Range	Accuracy	Repeatability		
Horizontal Scale					
54-060-024	0-24"/600mm	40µm	10µm (± 2s)		
Vertical Scale					
54-065-024	0-24"/600mm	40µm	10µm (± 2s)		
Horizontal/Vertical Scale					
54-070-024	0-24"/600mm	40µm	10µm (± 2s)		
54-115-333	Simplex Computer Connect Kit. Includes 80"(2m) connecting cable				
	with 9 pinIBM compatible; 9/25 pin adaptor, support disk & instruction				
	book.				
54-100-350	Replacement lithiur	Replacement lithium battery (type #CR2032 or BR2032).			