## Fowler



▲No. 52-225-015

## Depth Micrometers

Use Fowler Depth Micrometers for measuring the depth of small holes, small fabricated articles with grooved or elevated surfaces or different depths or heights. Particular attention has been paid in obtaining the accuracy of the contact surface of the rod and its straightness.

## **Special Features:**

- Accuracy from .0003"
- Clear microfine graduations .001" (.01mm) on satin chrome finish.
- Base of tool steel hardened, precision ground and microlapped. All other surfaces satin chrome finished.
- Base available in 2<sup>1</sup>/2" or 4" lengths.
- Quick and easy zero adjustment.
- Rods hardened, ground and lapped on measuring surfaces and adjustable in either direction. Measuring range per rod is 1" and .168" in diameter. Interchangeable rods are fitted to the micrometer spindle against a positive stop and locked.
- Ratchet thimble for consistent repeated accuracy.
- Threads hardened, ground and lapped for accuracy. Screw precision ground and lapped.
- Meets or exceeds Federal accuracy specifications.
- Price includes spanner wrench and fitted case.

Order No.	Range	Base Size	No. Rods
Inch Series:			
52-225-005	0—3"	<b>2</b> <sup>1</sup> ¦2"	3
52-225-006	0—4"	2 <sup>1</sup> ¦2"	4
52-225-010	0—3"	4"	3
52-225-011	0—4"	4"	4
52-225-015	0—6"	4"	6
52-225-020	0—6"	<b>2</b> <sup>1</sup> ¦2"	6
52-225-030	0—12"	<b>2</b> <sup>1</sup> ¦2"	12
52-225-035	0—12"	4"	12
Metric Series:			
52-225-075	0—75mm	62mm	3
52-225-150	0—150mm	100mm	6
52-225-300	0—300mm	100mm	12

