

## **▲** #52-385-012

Fowler's Combination Sets are useful for all mechanical jobs and are used as squares, height gages, depth gages, levels, marking gages, scribers, center gages, bevel protractors, steel rules and plumbs.

- Blades fully hardened and tempered.
- Protractor head has level.
- Reversible protractor heads.
- Blades in 4R (graduated in 8ths, 16ths, 32nds and 64ths) or 16R (graduated in 32nds, 64ths, 50ths and 100ths).
- Squares and center heads fully hardened.

- Available in metric—mm and .5mm graduations on one side, mm graduations on reverse side.
- Finished in baked blue enamel.
- Combination sets include square head, center head and reversible protractor head with 12", 18" or 24" blades. Double-indexed protractor graduated 180° in both directions
- Square head has level and scriber point.
- Squares and combination sets meet Federal Specifications Type VI, Class B.
- Easy-to-read satin chrome finish blades.
- Microfine graduations.
- Price includes fitted case.

=		
_		
		н
	_	н

Order No.	Blade Size	Graduation	Туре
Inch Size:			
52-385-012	12"	4R	Standard
52-385-112	12"	4R	Signature Edition
52-390-012	12"	16R	Standard
52-385-018	18"	4R	Standard
52-390-018	18"	16R	Standard
52-385-024	24"	4R	Standard
52-390-024	24"	16R	Standard
Metric Series:			
52-375-014	300mm	1mm-0.5mm	



184

		18	5	
	Fowle	Co	mbination Sc	quares
	Jun	1 Jul	uh	HARDENED HEADS
	MADE IN THE	Signature Edition 2 pc. Combination Set #52-388-112		3 pc. Combination Set #52-386-012
F	Order No.		Blade Size	Graduation
		Sets—Hardened Heads:		
	Inch Series:			
	52-386-006		6"	4R
	52-391-006		6"	16R
	52-386-012		12"	4R
	52-391-012		12"	16R
	52-386-018		18"	4R
	52-391-018		18"	16R
	52-386-024		24"	4R
	52-391-024		24"	16R
	Metric Series:			
	52-372-014	<b>0</b> / 11 1	300mm	1mm-0.5mm
		Sets—Hardened Heads:		
	Inch Series:	Type	0"	10
	52-388-006	Standard	6"	4R
	52-392-006	Standard	6"	16R
	52-388-012	Standard	12"	4R
	52-388-112	Signature Edition	12"	4R
	52-392-012 52-398-018	Standard	12"	16R
	52-388-018	Standard	18"	4R
	52-392-018	Standard	18"	16R
	52-388-024	Standard	24"	4R
	52-392-024	Standard	24"	16R
	Metric Series: 52-373-014	Standard	300mm	1mm-0.5mm
	52-3/3-014	Stanuaru	30011111	

