

Fowler

Sylvac Deluxe Electronic Protractor

Fowler-Sylvac's Deluxe Electronic Protractor, featuring the patented Sylvac measuring system, provides an LCD readout in 1 minute of arc or 0.01 degrees of arc. A push-button selects the range according to application (1 x 360°, 2 x 180° or 4 x 90°) and changes the reading from arc minutes to decimal degrees. Additional push-buttons provide "reset" and "print" functions.

Special Features:

- Includes 8" blade, V-base support stand, and fitted case.
- Direct RS232 output.
- Microfine adjustment for superior accuracy.
- Completely portable; battery-operation provides approximately two years of life.
- Hardened stainless steel blades
- Storage temperature: -20° to +70°C.
- Operational temperature: 41-104F, 5-40°C.
- Optional 6", 12" and 20" blades.
- Optional acute angle and internal angle attachments.
- Optional level attachment turns protractor into an electronic inclinometer.



Order No.	Order Description
54-440-977	Deluxe Protractor Set (with 8" blade, "V" base & case)
54-440-910	Acute angle attachment
54-440-920	6"/150mm blade
54-440-925	8"/200mm blade (included with Protractor)
54-440-930	12"/300mm blade
54-440-940	20"/500mm blade
54-100-350	Replacement lithium battery (type CR2032)
54-115-333	Simplex computer connecting kit. Includes 80"(2m) connecting cable with 9 pin IBM compatible, 9/25 pin adapto, support disk and instruction book.