



▲ Left to right: #53-422-057, #53-422-058 and #53-422-059.

**Wyler's Precision Frame Spirit** Levels are used for adjusting and checking horizontal and vertical surfaces and shafts. Sensitivity .0005" per 10". The Level features two prismatic sides. Also comes equipped with an insulating handle.

## **Special Features:**

- A clear view of the main vial can be observed not only from above but also from both sides. This full view allows position of the bubble to be read easily.
- The longitudinal vial which is set in a steel tube is not subject to the casting stresses of the usual, simple designs. Besides the other features, this makes for greater accuracy and reliability of the Fowler range.
- Price includes wooden case.
- Simple asjustment system.
- Stability of twist to ±5½.
- Fully in compliance with DIN standards.



			Sensitivity	Overall
Order No.	Inch	Metric	Angular	Dimensions
53-422-057	.0005"/10"	.05mm/m	10 sec.	6" x 1 <sup>9</sup> /64" x 6"
				(150mm x 35mm x 150mm)
53-422-058	.0005"/10"	.05mm/m	10 sec.	4" x 1 <sup>3</sup> /8" x 4"
				(100mm x 35mm x 100mm)
53-422-059	.0005"/10"	.05mm/m	10 sec.	7 <sup>7</sup> /8"x 1 <sup>5</sup> /8"x 7 <sup>7</sup> /8"
				(200mm x 40mm x 200mm)

Other sizes sensitivities and magnetic inserts available. Prices quoted upon request.