



## Euro-Depth Gages




Fowler's new Euro-Depth Gages feature Direct RS232 Output. These low cost tools combine Fowler's Swiss patented measuring system with the rugged design of a full 8" and 12" capacity depth gage. Together they replace conventional vernier and dial depth gages and depth micrometers.

### Specifications:

- Features a standard style end.
- Base width = .300"; beam width = .637"; beam thickness = .120".
- Large easy to read LCD display.
- Resolution: .0005" (.01mm)
- Direct inch/metric conversion.
- Incremental floating zero.
- Low drain, high efficiency lithium wafer battery (environmentally safe for disposal) offers 3000 hours of continuous on-time. Life extended 2—3 years with use of on/off switch.
- Price includes battery & deluxe wood case.

Range	Max Error	Squareness
8"	.0015"(.04mm)	.0006"(.015mm)
12"	.002"(.05mm)	.0012"(.03mm)



Order No.	Description
54-137-008	8"/200mm Euro-Depth Gages, base length = 4"/100mm.
54-137-012	12"/300mm Euro-Depth Gages, base length = 6"/150mm.
54-100-350	Replacement lithium battery (type CR2032 or BR2032).
54-115-333	Simplex Computer Kit. Includes 80" (2m) connecting cable 9 pin IBM ATRS-232 connector; GageWedge software support disk.