



EZ Read Rules



Features

- EZ Read Rules are constructed of hardened stainless steel.
- Etched, white numerals and graduations are easy to read against the non-glare, black finish.
- 3R inch graduations are in 32nds, 64ths, 10ths and 50ths.
- 4R inch graduations are in 8ths and 16ths on one side; reverse side of the rule is in 32ths and 64ths.
- 5R inch graduations are in 32nds and 64ths on one side; reverse side of the rule is in 10ths and 100ths.
- 16R inch graduations are in 32nds, 64ths, 50ths and 100ths.
- E/M graduations are .5mm, 1mm, 32nds, 64ths.
- Flexible rules are .020" thick.
- Rigid rules are .035" thick.

| Order No. | Size | Width | Grad. | Style |
|------------|------|-------|-------|----------|
| 52-297-006 | 6" | 1/2" | 4R | Flexible |
| 52-297-012 | 12" | 1/2" | 4R | Flexible |
| 52-297-018 | 18" | 3/4" | 4R | Flexible |
| 52-297-024 | 24" | 3/4" | 4R | Flexible |

| | | | | |
|------------|-----|------|----|----------|
| 52-298-006 | 6" | 1/2" | 3R | Flexible |
| 52-298-012 | 12" | 1/2" | 3R | Flexible |

| | | | | |
|------------|-----|------|----|----------|
| 52-307-006 | 6" | 1/2" | 5R | Flexible |
| 52-307-012 | 12" | 1/2" | 5R | Flexible |
| 52-307-018 | 18" | .76" | 5R | Flexible |
| 52-307-024 | 24" | .76" | 5R | Flexible |

| | | | | |
|------------|-----|------|-----|----------|
| 52-308-006 | 6" | 1/2" | 16R | Flexible |
| 52-308-012 | 12" | 1/2" | 16R | Flexible |
| 52-308-018 | 18" | .76" | 16R | Flexible |
| 52-308-024 | 24" | .76" | 16R | Flexible |

| | | | | |
|------------|------------|--------------|-----|----------|
| 52-379-006 | 6"(150mm) | 1/2"(12.5mm) | E/M | Flexible |
| 52-379-012 | 12"(300mm) | 1/2"(12.5mm) | E/M | Flexible |

| | | | | |
|------------|-----|-------|----|-------|
| 52-336-006 | 6" | 3/4" | 3R | Rigid |
| 52-336-012 | 12" | 1.03" | 3R | Rigid |

| | | | | |
|------------|-----|-------|----|-------|
| 52-337-006 | 6" | 3/4" | 4R | Rigid |
| 52-337-012 | 12" | 1.03" | 4R | Rigid |
| 52-337-018 | 18" | 1.2" | 4R | Rigid |
| 52-337-024 | 24" | 1.2" | 4R | Rigid |

| | | | | |
|------------|-----|-------|-----|-------|
| 52-338-006 | 6" | 3/4" | 16R | Rigid |
| 52-338-012 | 12" | 1.03" | 16R | Rigid |
| 52-338-018 | 18" | 1.2" | 16R | Rigid |
| 52-338-024 | 24" | 1.2" | 16R | Rigid |

| | | | | |
|------------|-----|-------|----|-------|
| 52-347-006 | 6" | 3/4" | 5R | Rigid |
| 52-347-012 | 12" | 1.03" | 5R | Rigid |
| 52-347-018 | 18" | 1.2" | 5R | Rigid |
| 52-347-024 | 24" | 1.2" | 5R | Rigid |

| | | | | |
|------------|------------|------------|-----|-------|
| 52-382-006 | 6"(150mm) | 3/4"(19mm) | E/M | Rigid |
| 52-382-012 | 12"(300mm) | 1.03" | E/M | Rigid |