

# Fowler

## Motorized Long-Travel UD Mark IV Indicator

- Features #54-520-788
- 0—12" (0—300mm) range
  - AGD Group 2 dimensional specifications. (3/8" mounting, standard backs, 4-48 thread).
  - Rugged housing constructed from high impact Polyamid, stainless steel shank and spindle.
  - Non-contact measuring system—no gears or pinions or moving parts.
  - Temperature range 41—104°F working; -4 to 140°F storage.
  - Repeatability .00012" (.003mm) ±2s
  - Resolution .0005" (.01mm)
  - Accuracy .0012" (.03mm)
  - Display face rotates 270° for easy viewing.
  - Measuring force 7-10 Newtons

### Electronic Features

- Completely reengineered measuring sensor. Direct inch/metric conversion. High contrast LCD display has indicators for in/mm, hold, reference, preset zero functions.
- Low drain, high efficiency lithium wafer battery—4500 hrs. continuous on time.
- Incremental floating zero. If tool is used for SPC, the zero button can automatically be configured as a data I/O switch.
- Hold feature freezes display for later viewing.



▲ Motorized version of the 54-520-788 Mark IV Ultra-Digit Indicator 0—12" (300mm). Granite stand not included.



Order No.	Description
54-520-788	Ultra-Digit Mark IV 0-12" (300mm). Motorized indicator only.
54-115-333	Simplex Computer Kit. Includes 80" (2m) connecting cable; 9 pin IBM AT RS-232 connector; software support disk; instruction manual.
54-100-350	Replacement lithium battery (type #CR2032 or BR2032).