

MICROMETERS

Outside Micrometers

Series 101



101-105



101-109

Features

- Satin-finished chrome frame, tapered (on the anvil side) for hard-to-reach places.
- Carbide-tipped measuring faces.

Accuracy

- Flatness: .000024"/0.6μm
- Parallelism:
 - .00005" for up to .59"/1.3μm for up to 15mm,
 - .00008" for up to 3"/2μm for up to 75mm,
 - .00012" for up to 4"/3μm for up to 100mm.
- Designed to be operated efficiently with one hand.



Designed to be operated efficiently with one hand.

Specifications

Outside Micrometers

Inch

Order No.	Range	Resolution	Accuracy	Remarks
101-230	0-.5"	.0001"	±.0001"	Ratchet Stop
101-113	0-1"	.0001"	±.0001"	Ratchet Stop
101-114	1-2"	.0001"	±.0001"	Ratchet Stop with Standard
101-119	2-3"	.0001"	±.0001"	Ratchet Stop with Standard
101-120	3-4"	.0001"	±.00015"	Ratchet Stop with Standard
101-117	0-1"	.0001"	±.0001"	Friction Thimble
101-118	1-2"	.0001"	±.0001"	Friction Thimble with Standard
101-105	0-1"	.001"	±.0001"	Ratchet Stop
101-106	1-2"	.001"	±.0001"	Ratchet Stop with Standard
101-109	0-1"	.001"	±.0001"	Friction Thimble
101-110	1-2"	.001"	±.0001"	Friction Thimble with Standard